

oor LIMITED WARRANTY

Main Door Corp. warrants that its product line of doors, sidelites, transoms and componentes shall be free from defects in materials and workmanship for a period of one year from the date of shipment to The Home Depot, provided that the Main Door Corp. product was properly installed, protected and maintained.

WHAT MAIN DOOR CORPORATION WILL DO:

Should a Main Door Corporation product fail to conform to its full written warranty*, Main Door Corporation will, at its option, either:

- 1. Repair the product found to be factory-defective;
- 2. Provide a replacement part or parts to repair the product found to be factory-defective;
- 3. Provide a replacement product in the same factory condition of fitting and finishing as the product that was originally ordered; or
- 4. Refund the homeowner, which will be processed by The Home Depot upon approval by Main Door Corp.
- * Full written warranty available at www.maindoorcorp.com

IN NO EVENT SHALL MAIN DOOR CORPORATION PAY FOR TRANSPORTATION, SHIPPING, LABOR OR INSTALLATION CHARGES OR COSTS INCURRED IN REPLACING DOORS, SIDELITES, TRANSOMS AND COMPONENTS OR FINISHING OF ANY ORIGINAL REPLACEMENT PRODUCT, ALL OF WHICH SHALL BE THE SOLE RESPONSIBILITY OF THE END-USER MAKING THE WARRANTY CLAIM.

***** IMPORTANT CONSIDERATIONS:

- All solid wood pre-hung and pre-finished exterior entry doors require adequate protection from the elements. Lack of proper overhang will void the warranty! The projected overhang depth must be equal or greater than ½ the overhang height for North and East facing doors and equal to the overhang height for South and West facing doors. Overhang width must be twice the width of the door (see graphic).
- Unfinished units must be sealed within 7 days of receipt.
- Storm door installation voids warranty.

CARE & MAINTENANCE:

Exposure to the elements, such as sun, wind, rain and any type of moisture will affect any well-finished exterior wood product. In order to preserve the beauty of your door and its protective finish, it is recommended to inspect the door at least once a year, and refinish it if necessary. It is considered normal maintenance to refinish the topcoat approximately once a year for those that have an overhang to protect the door.

2w

DEPTH OF OVERHANG FOR DOOR FACE DIRECTION			
NORTH	SOUTH	EAST	WEST
d = 1/2 h	d = h	d = 1/2 h	d = h

To maintain the topcoat, it will not be necessary to strip the door. To refinish, the unit must be cleaned of all dust and residue, given a light sanding the direction of the grain with 200-grit sandpaper. After sanding, wipe off all dust in the sanded areas. Thoroughly read and follow all instructions provided by the topcoat manufacturer on the can and apply accordingly.

WARRANTY CLAIM PROCESS:

Upon discovering that the door is defective or fails to conform to this one-year limited warranty, the homeowner MUST go to The Home Depot store within 24 to 48 hours of the date the defect was discovered, and file a Service Request Warranty Claim.

Once a Main Door Corporation (or representative) gets the written claim proof of purchase order number with the homeowner name, phone and address, it will exercise the option to inspect, repair, provide a replacement or refund the homeowner.

Main Door Corporation, California